



★ FASTENERS

Military-Fasteners.com

P/N NAS1005-8A

Description

Fastener Length: 1-9/64", Thread: 1/4-24, Thread Length: 21/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10058A
Minimum Qty (MOQ):	5
NSN:	5306-01-245-7179
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1005-8A Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.602 Inches Minimum And 0.662 Inches Maximum
Fastener Length:	1.117 Inches Minimum And 1.147 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.501 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1005 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1005-8A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.