

Description

Fastener Length: 1-63/64", Thread: 3/8-24, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100621
Minimum Qty (MOQ):	45 EA
NSN:	5306-01-259-8666
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1006-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.633 Inches Minimum And 0.693 Inches Maximum
Fastener Length:	1.960 Inches Minimum And 1.990 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.297 Inches Minimum And 1.327 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1006 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1006-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.