

Description

Fastener Length: 2-3/32", Thread: 3/8-24, Thread Length: 21/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS100623A
Minimum Qty (MOQ):	1
NSN:	5306-00-916-4461
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1006-23A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.663 Inches Minimum
Fastener Length:	2.101 Inches Nominal
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.438 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Special Features:	Tensile Strength At Room Temperature
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1006-23A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.