

Description

Fastener Length: 3-5/32", Thread: 3/8-24, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100640A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-613-0296
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1006-40A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.663 Inches Nominal
Fastener Length:	3.163 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
End Item Identification:	C5m Fuselage
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.485 Inches Minimum And 2.515 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Machine Hex Head
Special Features:	Undrilled Bolt
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1006-40A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.