



Military-Fasteners.com

P/N NAS1006-46

Description

Fastener Length: 3-17/32", Thread: 3/8-24, Thread Length: 3-17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100646
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-012-8362
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1006-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	3.538 Inches Nominal
Fastener Length:	3.538 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.875 Inches Nominal
Features Provided:	Unfinished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1006 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1006-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.