

Description

Fastener Length: 4-43/64", Thread: 3/8-24, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS100664A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-243-6139 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1006-64A Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.633 Inches Minimum And 0.693 Inches Maximum |
| Fastener Length: | 4.648 Inches Minimum And 4.678 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 3.985 Inches Minimum And 4.015 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1006 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1006-64A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.