

Description

Fastener Length: 2-19/32", Thread: 1/2-20, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS100828A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-990-1881
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1008-28A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.842 Inches Maximum
Fastener Length:	2.577 Inches Minimum And 2.607 Inches Maximum
Head Style:	Hexagon
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.751 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.735 Inches Minimum And 1.765 Inches Maximum
Features Provided:	Casehardened And Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1008-28A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.