

Description

Fastener Length: 1-1/32", Thread: 1/2-20, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS10083
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-321-4900
Schedule B:	7415.21.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1008-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.842 Inches Nominal
Fastener Length:	1.015 Inches Minimum And 1.045 Inches Maximum
Head Style:	Hexagon
Head Height:	0.265 Inches Minimum And 0.297 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.751 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.787 Inches Minimum First Hole And 0.807 Inches Maximum First Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	As-5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1008 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1008-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.