

Description

Fastener Length: 2-31/32", Thread: 1/2-20, Thread Length: 55/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS100834A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-225-2881 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1008-34A Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.812 Inches Minimum And 0.872 Inches Maximum |
| Fastener Length: | 2.952 Inches Minimum And 2.982 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.265 Inches Minimum And 0.297 Inches Maximum |
| Width Between Flats: | 0.741 Inches Minimum And 0.751 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Grip Length: | 2.110 Inches Minimum And 2.140 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 2nd Material Response Overall Or Ams 5733 Assn Std 3rd Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1008 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1008-34A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.