

**Description**

Fastener Length: 3-27/32", Thread: 1/2-20, Thread Length: 55/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS100848A
Minimum Qty (MOQ):	45 EA
NSN:	5306-00-007-0097
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1008-48A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.812 Inches Minimum And 0.872 Inches Maximum
<b>Fastener Length:</b>	3.827 Inches Minimum And 3.857 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.265 Inches Minimum And 0.297 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.751 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	2.985 Inches Minimum And 3.015 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5733 Assn Std 1st Material Response Overall Or Ams 5732 Assn Std 2nd Material Response Overall Or Ams 5737 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1008 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1008-48A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.