



Military-Fasteners.com

P/N NAS1010-14A

Description

Fastener Length: 1-59/64", Thread: 5/8-18, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS101014A
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-232-8201
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1010-14A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.012 Inches Minimum And 1.072 Inches Maximum
Fastener Length:	1.902 Inches Minimum And 1.932 Inches Maximum
Head Style:	Hexagon
Head Height:	0.328 Inches Minimum And 0.360 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.939 Inches Maximum
Nominal Thread Diameter:	0.625 Inches
Grip Length:	0.860 Inches Minimum And 0.890 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	18
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1010 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1010-14A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.