

Description

Thread Size: 3/16", Nut Height: 1/4", Head Width: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | NAS1021B3 |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5310-00-827-7233 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |
| National Motor Freight: | 093460, Bolts / Nuts Noi Bbc / Zinc |

NO IMAGE
AVAILABLE

P/N NAS1021B3 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Nut Height: | 0.250 Inches Nominal |
| Width Across Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | Not Rated |
| Nominal Thread Size: | 0.190 Inches |
| Bearing Surface Type: | Any Acceptable |
| Material: | Copper Alloy Nut |
| Material: | Plastic Polyamide Locking Insert |
| Surface Treatment: | Cadmium Nut |
| Specification/standard Data: | 80205-nas1021 Professional/industrial Association Standard |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1021B3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.