

**Description**

Thread Size: 5/32", Nut Height: 7/32", Head Width: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1021D08
Minimum Qty (MOQ):	30 EA
NSN:	5310-00-207-6589
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts

NO IMAGE  
AVAILABLE

## P/N NAS1021D08 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Nut Height:</b>	0.219 Inches Minimum And 0.239 Inches Maximum
<b>Width Across Flats:</b>	0.334 Inches Minimum And 0.346 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Aluminum Alloy Nut
<b>Material:</b>	Plastic Polyamide Locking Insert
<b>Surface Treatment:</b>	Anodize Nut

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1021D08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.