

Description

Thread Size: 1", Nut Height: 1-1/8", Head Width: 1-3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1021N17 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5310-00-325-1900 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1021N17 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 1.141 Inches Maximum |
| Width Across Flats: | 1.427 Inches Minimum And 1.440 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Uns |
| Thread Quantity Per Inch: | 14 |
| Nominal Thread Size: | 1.000 Inches |
| Countersink Angle: | 120.0 Degrees Nominal Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Nut |
| Surface Treatment: | Cadmium Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall Except Insert |
| Specification/standard Data: | 80205-nas1021 Professional/industrial Association Standard |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1021N17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.