

**Description**

Thread Size: 3/8", Nut Height: 9/32", Head Width: 35/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1022A6                                 |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5310-00-582-8448                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1022A6 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design                         |
| <b>Lubrication:</b>                                   | Dry Film Lubricant   |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 0.282 Inches Maximum                                       |
| <b>Width Across Flats:</b>                            | 0.553 Inches Minimum And 0.564 Inches Maximum              |
| <b>Temp Rating:</b>                                   | 450.0 Deg Fahrenheit Nominal                               |
| <b>Thread Series:</b>                                 | Unjf   |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Nominal Thread Size:</b>                           | 0.375 Inches   |
| <b>Countersink Angle:</b>                             | 120.0 Degrees Nominal Nut                                  |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced                                  |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches  |
| <b>Material:</b>                                      | Steel Overall  |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Fed Spec Single Treatment Response Overall        |
| <b>Specification/standard Data:</b>                   | 80205-nas1022 Professional/industrial Association Standard |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/NAS1022A6](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/NAS1022A6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.