

## **P/N NAS1022C8**

## **Description**

Thread Size: 1/2", Nut Height: 21/64", Head Width: 47/64

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS1022C8

Minimum Qty (MOQ): 5

NSN: 5310-00-879-0671


Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1022C8 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Nut Style:	Hexagon
Nut Height:	0.328 Inches Maximum
Width Across Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Steel Corrosion Resisting Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1022 Government Standard

## **How to Order**

Order this locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1022C8">https://military-fasteners.com/nuts/locknuts/NAS1022C8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1022C8">https://military-fasteners.com/nuts/locknuts/NAS1022C8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/locknuts/NAS1022C8">https://military-fasteners.com/nuts/locknuts/NAS1022C8</a> and selecting the quantity you want then click "add to cart".