

P/N NAS1022N16

Description

Thread Size: 1", Nut Height: 37/64", Head Width: 1-27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1022N16

Minimum Qty (MOQ): 5

NSN: 5310-00-776-1963

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1022N16 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.578 Inches Maximum
Width Across Flats:	1.427 Inches Minimum And 1.440 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	12
Hardness Rating:	35.0 Rockwell C Maximum
Nominal Thread Size:	1.000 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Surface Treatment:	Cadmium Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall Except Insert

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/NAS1022N16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.