

Description

Thread Size: 1/4", Nut Length: 1-9/32", Nut Height: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1023A4 |
| Minimum Qty (MOQ): | 45 EA |
| NSN: | 5310-00-989-7775 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1023A4 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 1.296 Inches Maximum |
| Nut Height: | 0.375 Inches Maximum |
| Plate Thickness: | 0.075 Inches Maximum |
| Plate Width: | 0.516 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.500 Inches Nominal |
| Center To Center Distance Between Mounting Holes Along Length: | 0.998 Inches Minimum And 1.002 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Countersink Angle: | 120.0 Degrees Nominal Nut |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ff-h-116,us2c Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1023 Professional/industrial Association Standard |

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1023A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.