

**Description**

Aluminium alloy - thread: 10-32, self-locking nutplate - two lug regular height, NAS1023 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | NAS1023D3         |
| Minimum Qty (MOQ):      | 2                 |
| NSN:                    | 5310-00-619-4345  |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE  
AVAILABLE

# P/N NAS1023D3 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Locking Feature:</b>   | Prevailing Torque With Nonmetallic Insert   |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum   |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.984 Inches Maximum  |
| <b>Nut Height:</b>  | 0.312 Inches Maximum  |
| <b>Plate Thickness:</b>   | 0.075 Inches Maximum  |
| <b>Plate Width:</b>   | 0.406 Inches Maximum  |
| <b>Nut Mounting Provision:</b>  | Straight Holes  |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.344 Inches Nominal  |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.686 Inches Minimum And 0.690 Inches Maximum   |
| <b>Temp Rating:</b>   | 250.0 Deg Fahrenheit Nominal  |
| <b>Thread Series:</b>   | Unjf  |
| <b>Thread Quantity Per Inch:</b>                                      | 32  |
| <b>Nominal Thread Size:</b>   | 0.190 Inches  |
| <b>Countersink Angle:</b>   | 120.0 Degrees Nominal Nut   |
| <b>Material:</b>  | Aluminum Alloy 2014 Shell Or Aluminum Alloy 2024 Shell  |
| <b>Material:</b>  | Plastic Polyamide Locking Insert  |
| <b>Surface Treatment:</b>   | Anodize Overall Except Insert Or Chromate Overall Except Insert   |
| <b>Surface Treatment Document And Classification:</b>                 | Mil-a-8625,type 1 Mil Spec 1st Treatment Response Overall Except Insert Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert |
| <b>Specification/standard Data:</b>                                   | 80205-nas1023 Professional/industrial Association Standard  |

## How to Order

Order this self-locking plate nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1023D3](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1023D3) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.