

## Description

Thread Size: 3/16", Nut Length: 1", Nut Height: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1024C3
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-816-7711
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1024C3 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.984 Inches Maximum
<b>Nut Height:</b>	0.378 Inches Maximum
<b>Plate Thickness:</b>	0.075 Inches Maximum
<b>Plate Width:</b>	0.453 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.344 Inches Nominal
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.686 Inches Minimum And 0.690 Inches Maximum
<b>Temp Rating:</b>	800.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Countersink Angle:</b>	99.0 Degrees Minimum Nut And 101.0 Degrees Maximum Nut
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1024 Professional/industrial Association Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1024C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.