

Description

Thread Size: 3/16", Nut Length: 1-5/64", Nut Height: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1026A3
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-857-2146
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1026A3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Nominal Mils And 0.103 Nominal Centimeters
Nut Style:	Plate
Nut Length:	1.093 Inches Maximum
Nut Height:	0.378 Nominal Centimeters
Plate Thickness:	0.075 Nominal Centimeters
Plate Width:	0.530 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	99.0 Degrees Minimum Nut And 101.0 Degrees Maximum Nut
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1026 Professional/industrial Association Standard

How to Order

Order this plate - one lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1026A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.