

## **P/N NAS1027A4**

### **Description**

Thread Size: 1/4", Nut Length: 29/32", Nut Height: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1027A4

Minimum Qty (MOQ): 15 EA

NSN: 5310-00-903-2552

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1027A4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.906 Inches Maximum
Nut Height:	0.375 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class1 Fed Std Single Treatment Response Overall Or Qq-p-416,type2,class2 Fed Std Single Treatment Response Overall Or Qq-p-416,type2,class3 Fed Std Single Treatment Response Overall

## **How to Order**

Order this plate - corner locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1027A4">https://military-fasteners.com/nuts/locknuts/NAS1027A4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.