

P/N NAS1030A4

Description

Thread Size: 1/4", Nut Length: 1", Nut Height: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1030A4

Minimum Qty (MOQ): 50 EA

NSN: 5310-00-823-8795

Schedule B: 7508.90.5000

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1030A4 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 1.038 Inches Maximum |
| Nut Height: | 0.375 Inches Maximum |
| Plate Thickness: | 0.075 Inches Maximum |
| Plate Width: | 0.516 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.339 Inches Minimum And 0.349 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Countersink Angle: | 120.0 Degrees Nominal Nut |
| Special Features: | Beveled Seat |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1030 Professional/industrial Association Standard |
| | |

How to Order

Order this plate - one lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/NAS1030A4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.