

**Description**

Thread Size: 1/2", Nut Height: 5/8", Nut Length: 1-19/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1031A8
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-799-5131
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1031A8 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.161 Inches Minimum And 0.166 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.602 Inches Maximum
<b>Nut Height:</b>	0.630 Inches Maximum
<b>Plate Thickness:</b>	0.115 Inches Maximum
<b>Plate Width:</b>	0.859 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.625 Inches Nominal
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	1.248 Inches Minimum And 1.252 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	20
<b>Nominal Thread Size:</b>	0.500 Inches
<b>Countersink Angle:</b>	120.0 Degrees Nominal Nut
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1031 Professional/Industrial Association Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.