

Description

Thread Size: 1/2", Nut Height: 5/8", Nut Length: 1-19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1031A8
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-799-5131
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1031A8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.161 Inches Minimum And 0.166 Inches Maximum
Nut Style:	Plate
Nut Length:	1.602 Inches Maximum
Nut Height:	0.630 Inches Maximum
Plate Thickness:	0.115 Inches Maximum
Plate Width:	0.859 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.625 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	1.248 Inches Minimum And 1.252 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.500 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1031 Professional/Industrial Association Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031A8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.