

Description

Thread Size: 7/64", Nut Length: 1", Nut Height: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS1031C04 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5310-00-411-6478 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093480, Bolts / Nuts Metal Silver Plated |



P/N NAS1031C04 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.984 Inches Maximum |
| Nut Height: | 0.218 Inches Maximum |
| Plate Thickness: | 0.075 Inches Maximum |
| Plate Width: | 0.416 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.344 Inches Nominal |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Temp Rating: | 800.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjc |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.112 Inches |
| Countersink Angle: | 120.0 Degrees Nominal Nut |
| Material: | Steel Corrosion Resisting Overall |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031C04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.