

**Description**

Thread Size: 7/64", Nut Length: 1", Nut Height: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1031C04
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-411-6478
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated



\* See page 2 for technical characteristics

## P/N NAS1031C04 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.984 Inches Maximum
<b>Nut Height:</b>	0.218 Inches Maximum
<b>Plate Thickness:</b>	0.075 Inches Maximum
<b>Plate Width:</b>	0.416 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.344 Inches Nominal
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.686 Inches Minimum And 0.690 Inches Maximum
<b>Temp Rating:</b>	800.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Countersink Angle:</b>	120.0 Degrees Nominal Nut
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031C04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.