

Description

Thread Size: 7/64", Nut Length: 1", Nut Height: 13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1031C04
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-411-6478
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated

NO IMAGE
AVAILABLE

P/N NAS1031C04 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.984 Inches Maximum
Nut Height:	0.218 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.344 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Corrosion Resisting Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031C04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.