

P/N NAS1031C5

Description

Thread Size: 19/64", Nut Length: 1-9/32", Nut Height: 21/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1031C5

Minimum Qty (MOQ): 10 EA

NSN: 5310-00-779-6769

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1031C5 Specifications

Thread Direction: Right-hand Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.421 Inches Minimum And 0.609 Inches Maximum Plate Width: 0.452 Inches Minimum And 0.609 Inches Maximum Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center: 0.495 Inches Minimum And 1.002 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Temp Racting: 800.0 Deg Fahrenheit Nominal Thread Series: 10njf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 9.312 Inches Material Document And Classification: 3737 Assn Std Single Material Response Overall	Thread Class:	3b
Locking Feature: Prevailing Torque All Metal Design Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Wildth: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: 5traight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center: 0.998 Inches Minimum And 0.505 Inches Maximum Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Tomad Series: Unif Features Provided: Floating Nut Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Silver Overall Silver Overall		
Mounting Hole Diameter: 0.130 Inches Minimum And 0.135 Inches Maximum Nut Style: Plate Nut Leight: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Gloss Jone Length: 800.0 Deg Fahrenheit Nominal Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Foating Nut Thread Quantity Per Inch: 24 Hardness Rating: 9.9.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Overall </th <th></th> <th></th>		
Nut Style: Nut Length: Nut Length: Nut Height: O. 328 Inches Maximum Plate Thickness: O. 045 Inches Maximum Plate Thickness: O. 045 Inches Maximum Plate Width: O. 412 Inches Minimum And 0.609 Inches Maximum Plate Width: Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: O. 998 Inches Minimum And 0.505 Inches Maximum O. 998 Inches Minimum And 1.002 Inches Maximum Thread Series: Features Provided: Thread Quantity Per Inch: Hardness Rating: Valuation Va	Locking Feature:	
Nut Length: 1.292 Inches Maximum Nut Height: 0.328 Inches Maximum Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Inch Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Overall	Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Height: Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Nut Mounting Provision: Nut Mounting Hole Arrangement Style: Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Nominal Thread Size: Material: Size: Material Document And Classification: Size: Siver Overall Siver Siver Overall Siver Siver Overall	Nut Style:	Plate
Plate Thickness: 0.045 Inches Maximum Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Allong Length: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 49.0 Rockwell C Maximum Nominal Thread Size: 10.312 Inches Material: 10.00 Americal Style: 10.00 Americal Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Surface Treatment: Silver Overall	Nut Length:	1.292 Inches Maximum
Plate Width: 0.412 Inches Minimum And 0.609 Inches Maximum Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Holes Along Length: 800.0 Deg Fahrenheit Nominal Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: 1ron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Nut Height:	0.328 Inches Maximum
Nut Mounting Provision: Straight Holes Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Thickness:	0.045 Inches Maximum
Mounting Hole Arrangement Style: 2 Holes Distance From Aperture Center To Mounting Hole Center: 0.495 Inches Minimum And 0.505 Inches Maximum Center To Center Distance Between Mounting Holes Along Length: 0.998 Inches Minimum And 1.002 Inches Maximum Temp Rating: 800.0 Deg Fahrenheit Nominal Thread Series: Unjf Features Provided: Floating Nut Thread Quantity Per Inch: 24 Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Plate Width:	0.412 Inches Minimum And 0.609 Inches Maximum
Distance From Aperture Center To Mounting Hole Center: Center To Center Distance Between Mounting Holes Along Length: Temp Rating: Bound Series: Unjf Features Provided: Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Material Document And Classification: Silver Sulface Treatment: O.495 Inches Minimum And 0.505 Inches Maximum O.998 Inches Minimum And 1.002 Inc	Nut Mounting Provision:	Straight Holes
Center To Center Distance Between Mounting Holes Along Length: Temp Rating: 10.998 Inches Minimum And 1.002 Inches Maximum 10.998 Inches Maxim	Mounting Hole Arrangement Style:	2 Holes
Holes Along Length: Temp Rating: 800.0 Deg Fahrenheit Nominal Unjf Features Provided: Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Material Document And Classification: Precious Material: Surface Treatment: Silver Overall	Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Thread Series: Floating Nut Thread Quantity Per Inch: Hardness Rating: Nominal Thread Size: Material: Iron Alloy 660 Overall Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Features Provided: Thread Quantity Per Inch: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Quantity Per Inch: Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Thread Series:	Unjf
Hardness Rating: 49.0 Rockwell C Maximum Nominal Thread Size: 0.312 Inches Material: Iron Alloy 660 Overall Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Precious Material: Silver Surface Treatment: Silver Overall	Features Provided:	Floating Nut
Nominal Thread Size: Material: Material: Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Thread Quantity Per Inch:	24
Material: Material Document And Classification: Precious Material: Surface Treatment: Iron Alloy 660 Overall Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Silver Silver Overall	Hardness Rating:	49.0 Rockwell C Maximum
Material Document And Classification: Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Precious Material: Silver Silver Overall	Nominal Thread Size:	0.312 Inches
Precious Material: Surface Treatment: 5737 Assn Std Single Material Response Overall Silver Silver Overall	Material:	Iron Alloy 660 Overall
Surface Treatment: Silver Overall	Material Document And Classification:	
	Precious Material:	Silver
Surface Treatment Document And Classification: Ams 2410 Assn Std Single Treatment Response Overall	Surface Treatment:	Silver Overall
	Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

