

Description

Thread Size: 27/64", Nut Height: 1/2", Nut Length: 1-15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1031C7
Minimum Qty (MOQ):	1 EA
NSN:	5310-00-829-3129
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1031C7 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.161 Inches Minimum And 0.166 Inches Maximum
Nut Style:	Plate
Nut Length:	1.477 Inches Maximum
Nut Height:	0.504 Inches Maximum
Plate Thickness:	0.115 Inches Maximum
Plate Width:	0.719 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.562 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	1.123 Inches Minimum And 1.127 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	20
Nominal Thread Size:	0.437 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Corrosion Resisting Overall
Precious Material And Location:	External Surface Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1031 Professional/Industrial Association Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1031C7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.