

Description

Thread Size: 1/4", Nut Height: 3/8", Nut Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1032A4
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-064-1827
Schedule B:	7318.16.0085
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1032A4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.316 Inches Maximum
Nut Height:	0.387 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.531 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.312 Inches Nominal
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1032 Professional/industrial Association Standard

How to Order

Order this slf lkg nut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1032A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.