

P/N NAS1032A4

Description

Thread Size: 1/4", Nut Height: 3/8", Nut Length: 1-5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1032A4

Minimum Qty (MOQ): 20 EA

NSN: 5310-00-064-1827

Schedule B: 7318.16.0085

ECCN: 9A991.

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1032A4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.316 Inches Maximum
Nut Height:	0.387 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.531 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.312 Inches Nominal
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1032 Professional/industrial Association Standard

How to Order

Order this slf lkg nut from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1032A4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.