

**Description**

Thread Size: 1/4", Nut Height: 3/8", Nut Length: 1-5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1032A4
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-064-1827
Schedule B:	7318.16.0085
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1032A4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.316 Inches Maximum
<b>Nut Height:</b>	0.387 Inches Maximum
<b>Plate Thickness:</b>	0.075 Inches Maximum
<b>Plate Width:</b>	0.531 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.500 Inches Nominal
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.312 Inches Nominal
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Countersink Angle:</b>	120.0 Degrees Nominal Nut
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1032 Professional/industrial Association Standard

## How to Order

Order this slf lkg nut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1032A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.