

## **P/N NAS1032C3W**

## **Description**

Thread Size: 3/16", Nut Length: 1-3/32", Nut Height: 19/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1032C3W

Minimum Qty (MOQ): 5 EA

NSN: 5310-00-903-2831

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1032C3W Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Welding Projection Quantity:	2
Nut Style:	Plate
Nut Length:	1.094 Inches Maximum
Nut Height:	0.312 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.422 Inches Maximum
Nut Mounting Provision:	Welding Projections
Mounting Provision Location:	Opposite Nut Projection Side
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Countersink Angle:	120.0 Degrees Nominal Nut
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Corrosion Resisting Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

### **How to Order**

Order this plate - one lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1032C3W">https://military-fasteners.com/nuts/locknuts/NAS1032C3W</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.