

Description

Thread Size: 5/32", Nut Length: 29/32", Nut Height: 21/64", NAS1033 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1033C08
Minimum Qty (MOQ):	1
NSN:	5310-00-010-8378
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated



* See page 2 for technical characteristics

P/N NAS1033C08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.170 Inches Minimum Nut And 0.185 Inches Maximum Nut
Mounting Hole Diameter:	0.098 Nominal Mils And 0.103 Nominal Centimeters
Nut Style:	Plate
Nut Length:	0.906 Inches Maximum
Distance From Base To Center Of Aperture:	0.281 Inches Nominal
Nut Height:	0.343 Nominal Centimeters
Plate Thickness:	0.075 Nominal Centimeters
Plate Width:	0.619 Inches Maximum
Nut Counterbore Depth:	0.070 Inches Nominal Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.484 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.250 Inches Nominal
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Corrosion Resisting Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1033 Professional/Industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/NAS1033C08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.