

**Description**

Thread Size: 5/32", Nut Length: 29/32", Nut Height: 21/64", NAS1033 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | NAS1033C08                               |
| Minimum Qty (MOQ):      | 1  |
| NSN:                    | 5310-00-010-8378                         |
| Schedule B:             | 7318.16.0085                             |
| ECCN:                   | EAR99                                    |
| National Motor Freight: | 093480, Bolts / Nuts Metal Silver Plated |



\* See page 2 for technical characteristics

# P/N NAS1033C08 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3b   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design                         |
| <b>Counterbore Diameter:</b>  | 0.170 Inches Minimum Nut And 0.185 Inches Maximum Nut      |
| <b>Mounting Hole Diameter:</b>  | 0.098 Nominal Mils And 0.103 Nominal Centimeters           |
| <b>Nut Style:</b>   | Plate  |
| <b>Nut Length:</b>  | 0.906 Inches Maximum                                       |
| <b>Distance From Base To Center Of Aperture:</b>                      | 0.281 Inches Nominal                                       |
| <b>Nut Height:</b>  | 0.343 Nominal Centimeters                                  |
| <b>Plate Thickness:</b>   | 0.075 Nominal Centimeters                                  |
| <b>Plate Width:</b>   | 0.619 Inches Maximum                                       |
| <b>Nut Counterbore Depth:</b>   | 0.070 Inches Nominal Nut                                   |
| <b>Nut Mounting Provision:</b>  | Straight Holes   |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes  |
| <b>Distance From Mounting Hole Center To Base:</b>                    | 0.484 Inches Nominal                                       |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.250 Inches Nominal                                       |
| <b>Temp Rating:</b>   | 800.0 Deg Fahrenheit Nominal                               |
| <b>Thread Series:</b>   | Unjc   |
| <b>Thread Quantity Per Inch:</b>                                      | 32   |
| <b>Nominal Thread Size:</b>   | 0.164 Inches   |
| <b>Material:</b>  | Steel Corrosion Resisting Overall                          |
| <b>Precious Material:</b>   | Silver   |
| <b>Surface Treatment:</b>   | Silver Overall   |
| <b>Surface Treatment Document And Classification:</b>                 | Ams 2410 Assn Std Single Treatment Response Overall        |
| <b>Specification/standard Data:</b>                                   | 80205-nas1033 Professional/Industrial Association Standard |

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/NAS1033C08](https://military-fasteners.com/nuts/self_locking+nutplates/NAS1033C08) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.