

Description

Thread Size: 3/16", Nut Length: 29/32", Nut Height: 21/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[NAS1033-C3](#)

SKU / Model:	NAS1033C3
Minimum Qty (MOQ):	5
NSN:	5310-00-791-4913
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1033C3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.193 Inches Minimum Nut And 0.208 Inches Maximum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.906 Inches Maximum
Distance From Base To Center Of Aperture:	0.266 Inches Minimum And 0.296 Inches Maximum
Nut Height:	0.343 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.619 Inches Maximum
Nut Counterbore Depth:	0.055 Inches Minimum Nut And 0.085 Inches Maximum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.469 Inches Minimum And 0.499 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.248 Inches Minimum And 0.252 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Corrosion Resisting Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1033 Professional/industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1033C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.