

## P/N NAS1056C6-009

### **Description**

Hole Diameter: 3/16", Diameter: 3/8", Thickness: 5/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1056C6009

Minimum Qty (MOQ): 30 EA

NSN: 5310-01-204-2173

Schedule B: 7318.29.0000

ECCN: 9A991

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1056C6-009 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.190 Inches Minimum And 0.196 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.085 Inches Minimum And 0.095 Inches Maximum
Overall Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A581 Assn Std Single Material Response Overall Or Astm A582 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1056 Professional/industrial Association Standard

## **How to Order**

Order this washer from our inventory online by visiting <a href="https://military-fasteners.com/washers/flat+washers/NAS1056C6-009">https://military-fasteners.com/washers/flat+washers/NAS1056C6-009</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.