

**Description**

Thread Size: 1/4", Nut Length: 37/64", Nut Height: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1067A4
Minimum Qty (MOQ):	30 EA
NSN:	5310-00-543-8997
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1067A4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.254 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.591 Inches Maximum
<b>Nut Height:</b>	0.281 Inches Maximum
<b>Plate Thickness:</b>	0.055 Inches Maximum
<b>Plate Width:</b>	0.437 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.062 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.276 Inches Minimum And 0.286 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Width:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1067 Professional/industrial Association Standard

## How to Order

Order this plate locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1067A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.