

Description

Thread Size: 7/64", Nut Length: 31/64", Nut Height: 9/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1068C04
Minimum Qty (MOQ):	5
NSN:	5310-00-959-5919
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1068C04 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.066 Inches Minimum And 0.071 Inches Maximum
Nut Style:	Plate
Nut Length:	0.498 Inches Maximum
Nut Height:	0.153 Inches Maximum
Plate Thickness:	0.140 Inches Maximum
Plate Width:	0.315 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.148 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.294 Inches Minimum And 0.298 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1068 Professional/Industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1068C04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.