

P/N NAS1068RA04L

Description

Thread Size: 7/64", Nut Length: 41/64", Nut Height: 9/64"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS1068RA04L

Minimum Qty (MOQ): 5 EA

NSN: 5310-01-131-2945

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1068RA04L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.651 Inches Maximum
Nut Height:	0.153 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.315 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.204 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.404 Inches Minimum And 0.408 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this plate - two lug locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/NAS1068RA04L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/locknuts/NAS1068RA04L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/locknuts/NAS1068RA04L and selecting the quantity you