

# **P/N NAS1068RC08M**

## **Description**

Thread Size: 5/32", Nut Length: 45/64", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS1068RC08M

Minimum Qty (MOQ): 40 EA

NSN: 5310-01-155-2573

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1068RC08M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.168 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.707 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.367 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.233 Inches Minimum And 0.235 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.466 Inches Minimum And 0.470 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Test Data Document:	81349-mil-i-7214 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Specification/standard Data:	80205-nas1068 Professional/industrial Association Standard

# **How to Order** Order this plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS1068RC08M">https://military-fasteners.com/nuts/locknuts/NAS1068RC08M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.