

P/N NAS1068RC4

Description

Thread Size: 1/4", Nut Length: 51/64", Nut Height: 9/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1068RC4
Minimum Qty (MOQ):	10
NSN:	5310-01-259-3591
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1068RC4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Nominal Mils And 0.103 Nominal Centimeters
Nut Style:	Plate
Nut Length:	0.801 Inches Maximum
Nut Height:	0.281 Nominal Centimeters
Plate Thickness:	0.032 Nominal Centimeters
Plate Width:	0.500 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.281 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.560 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.2500 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Precious Material And Location:	Overall Silver
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas1068 Professional/industrial Association Standard

How to Order

