



Military-Fasteners.com

P/N NAS1068RX3

Description

Thread Size: 3/16", Nut Length: 47/64", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1068RX3
Minimum Qty (MOQ):	25 EA
NSN:	5310-01-075-7122
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1068RX3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.739 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.249 Inches Minimum And 0.251 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1068 Professional/industrial Association Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS1068RX3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.