

Description

Collar part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1080AG12
Minimum Qty (MOQ):	80 EA
NSN:	5320-01-025-7820
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N NAS1080AG12 Specifications

Collar Outside Diameter:	0.596 Inches Minimum And 0.601 Inches Maximum
Collar Overall Height:	0.381 Inches Minimum And 0.396 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.373 Inches Minimum And 0.378 Inches Maximum
Collar Style:	Configural Type
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2219 Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1080 Professional/industrial Association Standard

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1080AG12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.