

**Description**

Collar part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1080AG12
Minimum Qty (MOQ):	80 EA
NSN:	5320-01-025-7820
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1080AG12 Specifications

<b>Collar Outside Diameter:</b>	0.596 Inches Minimum And 0.601 Inches Maximum
<b>Collar Overall Height:</b>	0.381 Inches Minimum And 0.396 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.373 Inches Minimum And 0.378 Inches Maximum
<b>Collar Style:</b>	Configural Type
<b>Heat Treatment:</b>	T-4 Solution Heat Treated Overall
<b>Material:</b>	Aluminum Alloy 2219 Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1080 Professional/industrial Association Standard

## How to Order

Order this collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/NAS1080AG12](https://military-fasteners.com/collars/pin_rivet+collars/NAS1080AG12) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.