

Description

Collar part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1080K05          |
| Minimum Qty (MOQ):      | 100 EA              |
| NSN:                    | 5320-00-580-8362    |
| Schedule B:             | 7616.10.1000        |
| ECCN:                   | 9A991               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

# P/N NAS1080K05 Specifications

|  |  |
|--|--|
| Collar Outside Diameter:                       | 0.256 Inches Minimum And 0.260 Inches Maximum  |
| Collar Overall Height:                         | 0.219 Inches Minimum And 0.234 Inches Maximum  |
| Lubrication:                                   | Cetyl Alcohol  |
| Collar Inside Diameter:                        | 0.168 Inches Minimum And 0.173 Inches Maximum  |
| Collar Style:                                  | Configural Type  |
| Material:                                      | Aluminum Alloy 2024 Overall  |
| Surface Treatment:                             | Anodize Overall Or Chromate Overall  |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall Or Mil-c-5541 Mil Spec Single Treatment Response Overall |
| Specification/standard Data:                   | 80205-nas1080 Professional/industrial Association Standard   |

## How to Order

Order this collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/NAS1080K05](https://military-fasteners.com/collars/pin_rivet+collars/NAS1080K05) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.