

Description

Collar part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1080K10
Minimum Qty (MOQ):	85 EA
NSN:	5320-01-125-5103
Schedule B:	7616.10.1000
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



\* See page 2 for technical characteristics

# P/N NAS1080K10 Specifications

Collar Outside Diameter:	0.506 Inches Minimum And 0.511 Inches Maximum
Collar Overall Height:	0.319 Inches Minimum And 0.334 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.330 Inches Minimum And 0.336 Inches Maximum
Collar Style:	Straight Type
Special Features:	Color Blue
Heat Treatment:	T-4 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1080 Professional/industrial Association Standard

## How to Order

Order this collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/NAS1080K10](https://military-fasteners.com/collars/pin_rivet+collars/NAS1080K10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.