



Military-Fasteners.com

P/N NAS1081-04D3L

Description

Fastener Length: 3/16", Thread: 4-40, Head Width: 3/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS108104D3L
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-319-2425
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1081-04D3L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Strip Threads
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.051 Inches Minimum And 0.061 Inches Maximum
Thread Quantity Per Inch:	40
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 4037 Fastener Or Steel Comp 4137 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8740 Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1081 Professional/industrial Association Standard

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/NAS1081-04D3L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.