P/N NAS1081-06B3

Description

Fastener Length: 3/16", Thread: 6-32, Head Width: 1/16", Thread Length: 5/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS108106B3
Minimum Qty (MOQ):	5
NSN:	5305-00-177-5500
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

* See page 2 for technical characteristics

P/N NAS1081-06B3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.136 Inches Minimum And 0.156 Inches Maximum
Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Pellet Threads Or Strip Threads
Point Style:	Cone
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.063 Inches Minimum And 0.064 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting https://military-fasteners.com/screws/setscrews/NAS1081-06B3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.